

Lanterna Drago

CA.NN.080.OTA.FI



Designer Roberto Cardin

N° LED	w	Lm to the light source	Luminous efficiency	Chromatic deviation	CRI	00 IP65		<b>R / V / B</b>	٩	
01	6	890	140Lm W	SDCM 2	80	80 total protection against the dust, splash water protection		-	-	2700K – 3000K – 4000K

The above data refer to a temperature of 3000k

Model	Description	Dimensions 720x500x210mm
	On-wall Led light body with wrought iron, n°1 Led lighting source. Finish: varnished faux corten, other colors on request. Diffusor: "pulegoso" blown glass light amber color with air bubbles incorporated in the thickness of the glass. It is provided with 1,5m cable for the electrical connection. Indoor/outdoor installation on any carrying plane surface that can hold a 10kg in embossed weight. Fixing by four screws with 6mm diameter not supplied by us.	T20 210/210

ELECTRICITY SUPPLY: 350mA constant current SELV POWER SUPPLY, not included, remotely placed.	Connection: Connector compliant withEN 60998-2-1							
Series electrical connection. POLARITY: RED Cable + BLACK Cable- / / BROWN Cable + light blue CABLE -	ATTENTION	IP68 connector						
	The protection degree of the	for outdoor use:						
	connection system must be	(FACSIMILE)						
	identical or greater than the							
	protection degree of the product.							
	The junction clips are not included.	and the second second second						
	The installation must be carried out							
	by qualified personnel.							
• ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. The connection to the electricity grid must be carried out only after completing the								

• ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. The connection to the electricity grid must be carried out only after completing the wiring of all the components. If this simply rule is not respected, the lighting source will be irremediably damaged. The installation must be carried out by qualified personnel.

(	C Compliant with Europe EMC – RoHS – REACH			It must not be provided with a electrical ground of protection	DIMMABLE By dimmable power supply	OPERATING TEMPERATURE -20°C +40°C	XX	collection of electric nic equipment	Made in Italy Projected, manufactured and assembled in Italy
	HI Proiect Srl	Via Mario Luci	ani 4/E - 3	2032 Feltre (BL)	Tel. 0439 310098	info@hiproiect.it	www.brillamenti.it	CF - PI e	n. isc. rea. imprese 00967030255



## **INSTALLATION AND USE MANUAL**

Carry out the holes for 6mm diameter screws (max 8mm)	Make watertight electrical junction, paying attent	tion to the polarity of the cables	Fix th	ne lamp				
	WARNING AND PROVISIONS							
ATTENTION   The appliance safety is guaranteed only by respecting, both during installation and employment phase, of the following instructions. It is therefore necessary to archive the present document.   WARNINGS:   • The power supply voltage must be removed during the installation and during any operation.   • The appliance must not be modified or tampered with in any way. Every modification can compromise the safety of the appliance, making it dangerous.   • The appliance tresponsibility of the manufacturer as well as the warranty.   • The appliance is free from the photobiological risk. Please follow the instructions of this data sheet.   • The pole is is damaged, it can be substituted only by the manufacturer. For further information please contact Hi.Project s.r.l.   • It the field bile power cables is damaged, it can be substituted only by the manufacturer or series of the product, at the eartifies necessary for the product to arrive free port at the manufacturer for repair.   • Warranty is void if the malfunction is due to: improper used the function site of a product, tampering, repairs not authorized by Hi. Project S.r.l. and/or in any case not compliant, the technical regulations that regulate the European market, damage caused by wrong connections or connections with an P degree lower than the product for Parent to the defetiveness of the product is organized by Hi. Project S.r.l. one head of the customer), other causes that are not expressly and unequivocally referred to the defetiveness of the product is reasport is organized by Hi. Project S.r.l. one product sare guaranteed for 24 months from the tansport is organized by Hi. Project S.r.l. one proved by Hi. Project S.r.l. and/or in								