


BRILLAMENTI





Ginestre

GI.NN.000.OTA.FI



N° LED	W	Lm ca	-(A)-	00	<u>~</u>	R/	V/B			1 -	
01	4	475	350mA	IP 65	DIFFUSE		-	-	-	3000 K	-

On-wall Led lamp.

It is provided with 25cm bipolar cable for the electrical connection.

Indoor/outdoor installation on any rigid surface.


Fixing by two screws not supplied by us.

FINISH: DARK BRONZE COLOR VARNISHED

DIFFUSOR: BLOWN GLASS LIGHT AMBER COLOR WITH INCLUDED AIR BUBBLES.

Ginestre

GI.NN.020.OTA.FI



N° LED	w	Lm ca	- A -	٥٥	<u> </u>	R/V/	В		-		1	
01	4	475	350mA	IP 65	DIFFUSE	-	:	-	-	- 30	000 K	-

On-floor Led lamp.

It is provided with 2m bipolar cable for the electrical connection.

Indoor/outdoor floor installation on a rigid and stable support sized not less than 150mmx150mm.

Fixing by four screws not supplied by us. FINISH: DARK BRONZE COLOR VARNISHED

DIFFUSOR: BLOWN GLASS LIGHT AMBER COLOR WITH INCLUDED AIR BUBBLES.