





lanternina

Photo © Manrico Dell'Agnola

Lanternina

CA.NN.000.OTA.FI - CA.NN.000.OTA.FI



150x210x90

N° LED (double emission)	W	Lm ca				R / V / B		
↑ 03	3,6	330	350mA / 24	IP40	DIFFUSE - 7° - 25° - 40°	-	-	2700K 3000K 4000K
↑ 07	8,4	770						
↓ 03	3,6	330	350mA / 24	IP40	DIFFUSE - 7° - 25° - 40°	-	-	2700K 3000K 4000K
↓ 07	8,4	770						

Aluminum and stainless steel Led light body for wall standing.
It is provided with 50cm bipolar cable for the electrical connection.
Indoor/outdoor installation on any rigid surface.

Fixing by screws not supplied by us.

FINISH: FRAME: CORTEN VARNISHED - WHITE RAL 9016 VARNISHED - CUSTOMIZED RAL VARNISHED

MASKING MIRRORS: WHITE RAL 9016 VARNISHED - CUSTOMIZED RAL VARNISHED

SCREEN: TRANSPARENT POLYCARBONATE

Lanternina

CA.NN.020.OTA.FI



150x210x90

N° LED	W	Lm ca				R / V / B		
14	16,8	1540	350mA / 24	IP65	DIFFUSE	-	-	2700K 3000K 4000K

Aluminum and stainless steel Led light body for wall standing.
It is provided with 50cm bipolar cable for the electrical connection.
Indoor/outdoor installation on any rigid surface.

Fixing by screws not supplied by us.

FINISH: CORTEN VARNISHED - WHITE RAL 9016 VARNISHED - CUSTOMIZED RAL VARNISHED

DIFFUSING MIRRORS: OPAL WHITE METHACRYLATE