



museum



Photo © Palais Mammig Museum




Photo © Manrico Dell'Agnola

Museum

MU.NN.000.OTA.FI

N° LED	W	Lm ca				R / V / B		
04	4,8	440	350mA / 24	IP20	DIFFUSE - 7° - 25° - 40°	-	-	2700K 3000K 4000K




310x35x52

On-wall/ceiling steel Led light body with directable light.
It is provided with 25cm bipolar cable for the electrical connection.
Indoor installation on any rigid plane surface.
Fixing by two screws not supplied by us.
FINISH: BLACK VARNISHED - CUSTOMIZED RAL VARNISHED

Museum

MU.NN.010.OTA.FI

N° LED	W	Lm ca				R / V / B		
20	24	2200	350mA	IP20	DIFFUSE - 7° - 25° - 40°	-	-	2700K 3000K 4000K



1560x35x52


On-wall/ceiling steel Led light body with directable light.
It is provided with 25cm bipolar cable for the electrical connection.
Indoor installation on any rigid plane surface.
Fixing by two screws not supplied by us.
FINISH: BLACK VARNISHED - CUSTOMIZED RAL VARNISHED



Photo © Brillamenti Officina della Luce

Museum

MU.NN.020.OTA.FI




310x40x52

N° LED	W	Lm ca				R / V / B		
04	4,8	440	350mA	IP20	DIFFUSE - 7° - 25° - 40°	-	-	2700K 3000K 4000K

On-wall/ceiling steel Led light body.
Number 4 Led mounted on swivel heads in every 20° directions independently.
It is provided with 25cm bipolar cable for the electrical connection.
Indoor installation on any plane rigid surface.
Fixing by two screws not supplied by us.
FINISH: BLACK VARNISHED - CUSTOMIZED RAL VARNISHED

Museum

MU.NN.030.OTA.FI



1590x50x70

N° LED	W	Lm ca				R / V / B		
20	24	2200	350mA	IP20	DIFFUSE - 7° - 25° - 40°	-	-	2700K 3000K 4000K

On-wall/ceiling steel Led light body.
Number 20 Led mounted on swivel heads in every 20° directions independently.
It is provided with 25cm bipolar cable for the electrical connection.
Indoor installation on any plane rigid surface.
Fixing by two screws not supplied by us.
FINISH: BLACK VARNISHED - CUSTOMIZED RAL VARNISHED

Museum

MU.NN.040.OTA.FI



140x110x52

N° LED	W	Lm ca				R / V / B		
05	6	550	350mA	IP20	DIFFUSE - 7° - 25° - 40°	-	-	2700K 3000K 4000K

Ceiling steel Led light body.
Number 4 Led mounted on swivel heads in every 20° directions independently, plus 1 central Led light not directable.
It is provided with 25cm bipolar cable for the electrical connection.
Indoor installation on any plane rigid surface.
Fixing by two screws not supplied by us.
FINISH: BLACK VARNISHED - CUSTOMIZED RAL VARNISHED

Museum

MU.NN.050.OTA.FI



110x110x50

N° LED	W	Lm ca				R / V / B		
05	6	550	350mA	IP20	DIFFUSE - 7° - 25° - 40°	-	-	2700K 3000K 4000K

Recessed ceiling steel Led light body.
Number 4 Led mounted on swivel heads in every 20° directions independently, plus 1 central Led light not directable.
It is provided with 25cm bipolar cable for the electrical connection.
Indoor installation on any plane rigid surface.
Fixing with torsion springs.
FINISH: BLACK VARNISHED - CUSTOMIZED RAL VARNISHED