



| N° LED | W | Lm to the light source | | | | R / V / B | | |
|--------|-----|---------------------------|-------|------|-----------------|-----------|---|-------------------|
| 03 | 3.6 | 330 | 350mA | IP40 | 7° - 25° - 40° | - | - | 2700K 3000K 4000K |
| 01 | 6,3 | 742 | 500mA | IP40 | 20° - 35° - 50° | - | - | 2700K 3000K 4000K |

| Model | Description | Dimensions 100 x 100 x 56mm | Fixing base Ø59,5mm |
|--|--|------------------------------|---------------------------|
| | Hanging Led light body in aluminum. Finish: white RAL 9016 varnished, other colors on request. Screen: transparent polycarbonate. It is provided with 2m transparent carrying cable for the electrical connection to the remote power supply. Indoor installation on any rigid surface. Fixing with two screws not supplied by us, with specific rosette. | | |
| | | | |
| Define the length of the suspension and fix the cable stopper by screwing the screw. | | Do the electrical connection | Fix the rosette by screws |

| | |
|---|--|
| Series electrical connection 350mA/500mA SELV. Polarity: Red cable + Black cable - | Connection: Connector compliant with EN 60998-2-1 standards (FACSIMILE) |
| | |

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

| | | | | | | |
|--|--|---|---|--|--|--|
| | Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD)) | CLASS III Operating with SELV | POWER SUPPLY By remote power supply SELV OUTPUT 350mA/500mA constant current | | Separate waste collection of electric and electronic equipment | Made in Italy Projected, manufactured and assembled in Italy |
|--|--|---|---|--|--|--|