



N° LED	W/mt	Lm/metro to the light source				R / V / B		
060	15	-	24V	IP40	DIFFUSE	-	RGB	- - -
140	15	1800	24V	IP40	DIFFUSE	-	-	2700K 3000K 4000K

Model	Description	Dimensions 16 x 7 x L mm	Bracket 987004	Bracket fixing
	On-wall/ceiling Led bar with aluminum terminals. Finish: anodized aluminum silver grey color. Screen: opal/transparent. It is provided with 25cm bipolar cable for the electrical connection. Maximum length bar 2000mm (longer lengths on request). Indoor installation on any flat and rigid surface with suitable brackets. Fixing by countersunk screws with maximum diameter 3 mm suitable to the support not supplied by us.			

Define the bar positioning	Fix the brackets maintaining a straight line	Carry out the electrical connection and insert the bar on the brackets	Final result

<p>Parallel electrical connection 24V Polarity: RED cable + BLACK cable -</p>	<p>ONLY FOR 24V RGB Connection to the pilot module</p> <p>Negative = red Negative = blue Negative = green Positive = black</p>	<p>Connection: Connector compliant with EN 60998-2-1</p> <p>(FACSIMILE)</p>
---	--	--

ATTENTION: Before starting all electrical connections, make sure that the power supply is not in voltage. If this simple rule is not respected, the lighting source will be irretrievably damaged.

	Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	CLASS III Operating with SELV	POWER SUPPLY By remote power supply SELV OUTPUT 24Vdc constant voltage / Only for 24Vdc RGB version, please see the connection to the pilot module		Separate waste collection of electric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy
--	--	---	---	--	--	--