

N° LED	W	Lm to the light source				R / V / B		
060	15	-	24V	IP40	DIFFUSE	-	RGB	- - -
140	15	1800	24V	IP40	DIFFUSE	-	-	2700K 3000K 4000K
128	23	3200	24V	IP40	DIFFUSE	-	-	2700K 3000K 4000K

Model	Description	Dimensions 60x40x 1175 mm	Suspension lamp	Accessories
	<p>Suspension Led lamp in Corian® or aluminum. Finish: white color. Screen: opal/transparent. It is provided with 2m bipolar cable transparent or covered with fabric black, red, streaked grey and white, for the electrical connection to the power supply. Maximum length: 1175mm. Indoor installation on any rigid surface. The bar is suspended with two steel cables. Fixing with screws suitable to the support with maximum diameter 4mm not supplied by us.</p>	<p>60x40x1175</p>		4641-M
				95227
				96339

Parallel electrical connection 24V Polarity: <b>RED cable +</b> <b>BLACK cable -</b>	ONLY FOR 24V RGB Connection to the pilot module	Connection: Connector compliant with EN 60998-2-1
	<p>Negative = red Negative = blue Negative = green Positive = black</p>	<p>(FACSIMILE)</p>

**ATTENTION:** Before starting all electrical connections, make sure that the power supply is not in voltage. If this simply rule is not respected, the lighting source will be irretrievably damaged.

<p><b>Compliant with European standards</b> (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))</p>	<p><b>CLASS III</b> Operating with SELV</p>	<p><b>POWER SUPPLY</b> By remote power supply SELV OUTPUT 24Vdc constant voltage / Only for 24Vdc RGB version, please see the connection to the pilot module</p>	<p>Separate waste collection of electric and electronic equipment</p>	<p><b>Made in Italy</b> Projected, manufactured and assembled in Italy</p>
--	---	--	---	--