

Cubetto

CU.NN.000.OTA.FI



N° LED	W	Lm to the light source	- A -		4	R/V/B				
03	10,5	-	350mA See the pilote module	IP40	DIFFUSE -40°	-	RGB	-	-	-
07	8.4	770	350mA	IP40	7° - 25° - 40°	-	-	2700K	3000K	4000K

Model		Description	Dimensions 100 x 1	100 x 56mm	Fixing rosette Ø89mm
	Finish: wh request. S It is provid electrical Indoor ins	Led light body in aluminum. Lite RAL 9016 varnished, other colors on screen: opal / transparent polycarbonate. Lited with 50cm bipolar cable for the connection to the power supply. Lited lation on any rigid plane surface. Lited wo screws not supplied by us.	[100x100	1	

Connector compliant with EN 60998-2-1 standards	Connection to the pilot module
(FACSIMILE)	+ = red - = red/black + = blue - = blue/black + = green - = green/black
	·

After making the electrical connection, rotate the lighting body two or

three turns anticlockwise

CE

Compliant with European standards

(EMC, RoHs, Ecodesign and requirements specified in the Low Voltage Directive (LVD))

CLASS IIIOperating with SELV

POWER SUPPLY

By remote power supply SELV OUTPLIT 350m

By remote power supply SELV OUTPUT 350mA constant current / Only for 350mA RGB version, please see the connection to the pilot module



Separate waste collection of electric and electronic equipment

Made in Italy
Projected, manufactured and assembled

Fixing the rosette to the ceiling with countersunk screws

maximum diameter 5mm

Screw the lighting body on the rosette