


## **Cubetto**

## CU.NN.000.OTA.FI




N° LED	W	<b>Lm</b> to the light source	- <b>A</b> -		<u> </u>	R/V/B				
03	10,5	-	350mA See the pilote module	IP40	DIFFUSE -40°	-	RGB	-	-	-
01	9	1060	500mA	IP40	20°- 35° - 50°	-	-	2700K	3000K	4000K


Model	Model Description		Dimensions 100 x 100 x 56m	m Fixing rosette Ø89mm
On-ceiling Led light body in aluminum. Finish: white RAL 9016 varnished, other colors on request. Screen: opal / transparent polycarbonate. It is provided with 50cm bipolar cable for the electrical connection to the power supply. Indoor installation on any rigid plane surface. Fixing by two countersunk screws with maximum diameter 5mm suitable to the fixing support, not supplied by us.		[2] 100x100		



Fixing the rosette to the ceiling with countersunk screws maximum diameter 5mm



After making the electrical connection, rotate the lighting body two or three turns anticlockwise



Screw the lighting body on the rosette

Series electrical connection 350mA/500mA SELV.	Connection:	ONLY FOR RGB VERSION	
Polarity: Red cable + Black cable -	Connector compliant with EN 60998-2-1 standards	Connection to the pilot module	
	(FACSIMILE)	+ = red - = red/black + = blue - = blue/black + = green - = green/black	
ATTENTION: Before starting all electrical connections, r	make sure that the power supply is not powered. If this simply rule is not respected, the li	ghting source will be irremediably damaged.	

( (

Compliant with European standards
(EMC, RoHs, Ecodesign and requirements specified in the Low Voltage
Directive (LVD))

CLASS III
Operating with SELV

**POWER SUPPLY**By remote power supply SELV OUTPUT 350mA/500mA constant current /
Only for 350mA RGB version, please see the connection to the pilot module



Separate waste collection of electric and electronic equipment Made in Italy
Projected, manufactured and assembled
in Italy