













N° LED	W	Lm to the light source				R / V / B		
03	38	4300	700mA	IP65	20° - 52°	-	-	2700K 3000K 4000K
36	36	3600	12V	IP65	DIFFUSE - 7° - 25° - 40°	-	RGB	- - -

Model	Description	Dimensions Ø 149 x 104mm
	<p>Aluminum Led floodlight, on-wall/ceiling/floor.</p> <p>Metal cable gland, it provided with 50cm neoprene cable for the electrical connection.</p> <p>Outdoor installation on any rigid surface by aluminum bracket.</p> <p>Fixing by one screw.</p>	

<p>Series electrical connection 350mA/700mA SELV. Polarity: Red cable + Black cable -</p>	<p>Parallel electrical connection 12V / 24V. Polarity: Red cable + Black cable -</p>	<p>Connection: Connector compliant with EN 60998-2-1 standards Connection to be made in a watertight place</p>
		<p>(FACSIMILE)</p>  <p>IP68 connector for example Steab Paguro 5664 or similar</p>

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

 <p>Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))</p>	<p>CLASS III Operating with SELV</p>	<p>POWER SUPPLY By remote power supply SELV OUTPUT 350mA constant current / By remote power supply SELV OUTPUT 24V constant voltage</p>	 <p>Separate waste collection of electric and electronic equipment</p>	<p>Made in Italy Projected, manufactured and assembled in Italy</p>
--	---	--	---	--