

N° LED	W	Lm to the light source				R / V / B		
01	9	1060	500mA	IP40	20° - 35° - 50°	-	-	2700K 3000K 4000K
03	10,5	-	350mA See the pilot module	IP40	DIFFUSE - 15° - 40°	-	RGB	- - -

Model	Description	Dimensions Ø88 x108 mm	Fixing support Ø63mm
	On ceiling Led light body in aluminum. Single emission. Finish: white RAL 9016 varnished, customized RAL varnished. Screen: opal / transparent polycarbonate. It is provided with 25cm bipolar cable for the electrical connection. Indoor ceiling installation. Fixing by two screws not supplied by us.		

Fix the rosette by screws	Do the electrical connection and screw the Led lighting body	Final result

Series electrical connection 350 - 500mA SELV. Polarity: Red cable + Black cable -	Connection: Connector compliant with EN 60998-2-1 standards	ONLY FOR RGB VERSION Connection to the pilot module
	(FACSIMILE) 	+ = red - = red/black + = blu - = blue /black + = green - = green/black

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	CLASS III Operating with SELV	ALIMENTAZIONE By remote power supply SELV OUTPUT 350mA/500mA constant current / For 350mA RGB version, please see the pilot module connection	Separate waste collection of electric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy
--	---	--	--	--