



N° LED double emission	W	Lm to the light source				R / V / B		
01	9	1060	500mA	IP40	DIFFUSE - 20° - 35° - 50°	-	-	2700K 3000K 4000K

Model	Description	Hole for fixing Ø50mm	Dimensions Ø60 x 155mm
	Ceiling recessed Led light body in aluminum. Finish: white RAL 9016 varnished, other colors on request. Screen: opal / transparent polycarbonate. It is provided with 25cm bipolar cable for the electrical connection. Indoor installation: on drywall with hole Ø50mm, thickness drywall 13mm, useful depth 60mm. Assembly with torsion springs.	 Hole Ø 50 mm	
Drill the ceiling Ø 50 mm	Carry out the electrical connection respecting the polarity and insert in position	Final result	

<b>Series electrical connection 350mA/500mA SELV. POLARITY: RED cable + BLACK cable -</b>	<b>Connection:</b> connector compliant with EN 60998-2-1 standards
	(FACSIMILE) 

**ATTENTION:** Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

<b>Compliant with European standards</b> (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	<b>CLASS III</b> Operating with SELV	<b>ALIMENTAZIONE</b> By remote power supply SELV OUTPUT 350mA/500mA constant current	Separate waste collection of electric and electronic equipment	<b>Made in Italy</b> Projected, manufactured and assembled in Italy
--	---	---	--	--