



N° LED double emission	W	Lm to the light source				R / V / B		
↑03	3.6	330	350mA	IP40	DIFFUSE	-	-	2700K 3000K 4000K
↓01	6.5	740	350mA	IP40	DIFFUSE - 20° - 35° - 50°	-	-	2700K 3000K 4000K

Model	Description	Dimensions Ø60 x 600mm	Rosette Ø80mm
	Aluminum Led body light for ceiling hanging. Finish: white RAL 9016 varnished, customized RAL varnished. Screen: transparent polycarbonate. It is provided with 2m carrying transparent cable for the electrical connection. Indoor installation on any rigid surface. Fixing by two screws (not supplied by us) with specific rosette.		
Define the length of the suspension and fix the cable stopper by screwing the screw.		Do the electrical connection	Fix the rosette by screws with maximum diameter 4mm.

<p>Series electrical connection 350mA SELV.</p> <p>Polarity: RED cable + BLACK cable -</p>	<p>Connection:</p> <p>Connector compliant with EN 60998-2-1 standards</p>
	(FACSIMILE)

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

	<p>Compliant with European standards</p> <p>(EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))</p>	<p>CLASS III</p> <p>Operating with SELV</p>	<p>POWER SUPPLY</p> <p>By remote power supply SELV OUTPUT 350mA constant current.</p>		<p>Separate waste collection of electric and electronic equipment</p>	<p>Made in Italy</p> <p>Projected, manufactured and assembled in Italy</p>
--	---	--	--	--	---	---