

N° LED	W	Lm to the light source				R / V / B		
03	10,5	-	350mA See the pilote module	IP65	DIFFUSE - 40°	-	RGB	- - -
07	8,4	770	350mA	IP65	7° - 25° - 40°	-	-	2700K 3000K 4000K

Model	Description	Assembly	Accessories: stake and supports	Dimensions 100 x 100 x 56mm
	<p>On-ceiling/wall/floor/on a stake/on a support Led light body in aluminum. Finish: white RAL 9016 varnished, other colors on request. Screen: opal/transparent polycarbonate. It is provided with 50cm neoprene cable for the electrical connection to the remote power supply. Indoor/outdoor installation on any rigid surface with stainless steel bracket. Fixing by one M6 screw not supplied by us.</p>	<p>Adjust the inclination and lock with the M5 Allen screw. Fixing to the support with M6 screw.</p>	<p>1000 Ø 20 400 Ø 20 50x100x4mm 400 Ø 20 50x100x4mm</p>	<p>56 125 100x100</p>

<p>Series electrical connection 350mA SELV. Polarity: RED cable + BLACK cable -</p>	<p>Connection: Connector compliant with EN 60998-2-1 standards</p>		<p>ONLY FOR RGB VERSION Connection to the pilot module</p>
	<p>(FACSIMILE) IP68 connector for example Steab Paguro 5664 or similar</p>	<p>(FACSIMILE) Indoor connector</p>	<p>+ = red - = red/black + = blue - = blue/black + = green - = green/black</p>

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

<p>Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))</p>	<p>CLASS III Operating with SELV</p>	<p>POWER SUPPLY By remote power supply SELV OUTPUT 350mA constant current / Only for 350mA RGB version, please see the connection to the pilot module</p>	<p>Separate waste collection of electric and electronic equipment</p>	<p>Made in Italy Projected, manufactured and assembled in Italy</p>
--	---	--	---	--