

Cubetto CU.NN.020.OTA.FI



N° LED	w	Lm to the light source	- <u></u>	٥٥	<u>A</u>	R/V/ B				
03	10,5	-	350mA See the pilote module	IP65	DIFFUSE - 40°	-	RGB	-	-	
01	9	1060	500mA	IP40	20°- 35° - 50°	-	-	2700K	3000K	4000K

Model	Description	Assembly	Accessories: stake and supports	Dimensions 100 x 100 x 56mm
	On-ceiling/wall/floor/on a stake/on a support Led light body in aluminum. Finish: grey / black anodized, other colors on request. Screen: opal/transparent polycarbonate. It is provided with 50cm neoprene cable for the electrical connection to the remote power supply. Indoor/outdoor installation on any rigid surface with stainless steel bracket. Fixing by one M6 screw not supplied by us.	Adjust the inclination and lock with the M5 Allen screw. Fixing to the support with M6 screw.	0001	100x100

	ectrical connection 350mA/500mA SELV. plarity: RED cable + BLACK cable -	Connection: Connector compliant with EN 60998-2-1 standards			ONLY FOR RGB VERSION Connection to the pilot module	
		IP68 con	(FACSIMILE) nector for example Steab Paguro 5664 or similar	FACSIMILE) Indoor connector	+ = red - = red/black + = blue - = blue/black + = green - = green/black	
	ATTENTION: Before starting all electrical conne	ections, make sur	e that the power supply is not powered. If this simply rule is	s not respected, the lighting source will	be irremediably damaged.	
CE	Compliant with European standards (EMC, RoHs, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	CLASS III Operating with SELV	POWER SUPPLY By remote power supply SELV OUTPUT 350mA/500mA constant current / Only for 350mA RGB version, please see the connection to the pilot module	Separate waste collection of electric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy	
HI Pro	iect Srl Via Mario Luciani 4/E - 32032 Feltre (BL)	Tel (1439 310098 info@hiproject.it	www.brillamenti.it	CF - PLe n. isc. rea. imprese 00967030255	