




N° LED	W	Lm to the light source				R / V / B				
01	12.6	1433	700mA	IP65	25° - 52°	-	-	2700K	3000K	4000K
03	3.6	330	350mA/24V	IP65	DIFFUSE - 7° - 25° - 40°	-	-	2700K	3000K	4000K
03	3.6	-	12V	IP65	DIFFUSE	-	RGB	-	-	-
07	8.4	770	350mA/24v	IP65	DIFFUSE - 7° - 25° - 40°	-	-	2700K	3000K	4000K

Model	Description	Dimensions Ø60 x 82 x 95 mm
	<p>Anti-blinding Led floodlight in aluminum for wall/ceiling/floor standing. It is provided with 50cm neoprene cable for the electrical connection. Indoor/outdoor installation on any rigid surface by stainless steel bracket. Fixing by one screw.</p> <p><b>** In outdoor spaces using exclusively with low beam light.</b></p>	



<p>Series electrical connection 350/700mA SELV. Polarity: <b>Red cable +</b> Black cable -</p>	<p>Parallel electrical connection 12V / 24V. Polarity: <b>Red cable +</b> Black cable -</p>	<p>IP68 connector for example Steab Paguro 5664 or similar. Connector compliant with EN 60998-2-1 standards</p>
		<p>(FACSIMILE)</p> <p>Connection to be made in a watertight place</p>

**ATTENTION:** Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

<p><b>Compliant with European standards</b> (EMC, RoHs, Ecodesign and requirements specified in the Low Voltage Directive (LVD))</p>	<p><b>CLASS III</b> Operating with SELV</p>	<p><b>POWER SUPPLY</b> By remote power supply SELV OUTPUT 350mA constant current / By remote power supply SELV OUTPUT 24V constant voltage</p>	<p>Separate waste collection of electric and electronic equipment</p>	<p><b>Made in Italy</b> Projected, manufactured and assembled in Italy</p>
--	---	--	---	--