



N° LED	W	Lm to the light source				R / V / B		
01	9	1060	500mA	IP40	20°-35°- 50°	-	-	2700K 3000K 4000K
03	10,5	-	350mA	IP40	DIFFUSE - 40°	-	RGB	- - -
07	8,4	770	350mA	IP40	7°-25°-40°	-	-	2700K 3000K 4000K

Model	Description	Fixing of the led lighting body with 5 mm diameter screw	Electrical connection	Dimensions Ø60 x 95 mm
	On-wall/ceiling or on a support Led floodlight in aluminum. Finish: black anodized - other colors on request. Screen: opal/transparent thick polycarbonate. It is provided with 1m neoprene cable for the electrical connection. Indoor installation on any rigid surface by specific stainless-steel bracket. Fixing by one screw with maximum diameter 5mm not supplied by us. Fixing the floodlight on the accessories with M5 screw supplied by us.	 Adjust the inclination with knurled linchpin	 - +	 120 90 Ø60

BC.015.010 Friction socket	SP.030.030 Support spacer	SP.045.050 Socket-spacer for the electrical connections	SP.O50.100	SP.V50.100
 Ø15x9.5mm Fixing of the socket by screws with 5mm diameter	 Ø30x30mm Fixing of the spacer by screws with 5mm diameter	 Ø45x50mm Fixing of the spacer by screws with 5mm diameter	 400 Ø20 50x100x4mm Fixing of the support by screws with 5mm diameter	 400 Ø20 50x100x4mm Fixing of the support by screws with 5mm diameter

Series electrical connection 350mA-500mA SELV. Polarity: Red cable + Black cable -	Connection: Connector compliant with EN 60998-2-1 standards		ONLY FOR RGB VERSION Connection to the pilot module
	(FACSIMILE) IP68 connector for example Steab Paguro 5664 or similar 	(FACSIMILE) Indoor connector 	+ = red - = red/black + = blue - = blue/black + = green - = green/black

**ATTENTION:** Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

	<b>Compliant with European standards</b> (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	<b>CLASS III</b> Operating with SELV	<b>POWER SUPPLY</b> By remote power supply SELV OUTPUT 350mA/500mA constant current / Only for 350mA RGB version, please see the connection to the pilot module	 Separate waste collection of electric and electronic equipment	<b>Made in Italy</b> Projected, manufactured and assembled in Italy
--	--	---	---	--	--