


N° LED	W	Lm to the light source				R / V / B		
01	1.2	110	350mA	IP65	DIFFUSE - 7° - 25° - 40°	-	RGB	2700K 3000K 4000K
03	3.6	330	350mA/24V	IP65	DIFFUSE - 7° - 25° - 40°	-	-	2700K 3000K 4000K

Model	Description	Dimensions Ø38 x 55 mm
	On wall/ceiling/floor Led floodlight in aluminum. It is provided with 50cm neoprene cable for the electrical connection. Indoor/outdoor installation on any rigid surface by specific stainless steel bracket. Fixing by one screw.	



<p>Series electrical connection 350mA SELV. Polarity: Red cable + Black cable -</p>	<p>Parallel electrical connection 12V / 24V. Polarity: Red cable + Black cable -</p>	<p>IP68 connector for example Steab Paguro 5664 or similar. Connector compliant with EN 60998-2-1 standards (FACSIMILE)</p>
<p>Connection to be made in a watertight place</p>		

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simple rule is not respected, the lighting source will be irretrievably damaged.

<p>Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))</p>	<p>CLASS III Operating with SELV</p>	<p>POWER SUPPLY By remote power supply SELV OUTPUT 350mA constant current / By remote power supply SELV OUTPUT 24V constant voltage</p>	<p>Separate waste collection of electric and electronic equipment</p>	<p>Made in Italy Projected, manufactured and assembled in Italy</p>
--	---	--	---	--