



N° LED	W/mt	Lm to the light source				R / V / B				
060	15	-	24V	IP40	DIFFUSE	-	RGB	-	-	-
120	15	1200	24V	IP40	DIFFUSE	-	-	2700K	3000K	4000K
128	23	3200	24V	IP40	DIFFUSE	-	-	2700K	3000K	4000K

Model	Description	Dimensions 24 x 35 x L mm
	<p>On-wall/ceiling Led bar, hanging available reducing electric power, aluminum terminals.</p> <p>It is provided with 20cm bipolar cable for the electrical connection.</p> <p>Maximum length 2000mm included terminals.</p> <p>Indoor installation on any plane and rigid surface by specific hooking. Fixing by screws not supplied by us.</p>	

<p>Parallel electrical connection 12V/24V</p> <p>Polarity: RED cable + BLACK cable -</p>	<p>Connection:</p> <p>Connector compliant with EN 60998-2-1 standards</p> <p>(FACSIMILE)</p>
--	---

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

	<p>Compliant with European standards (EMC, RoHs, Ecodesign and requirements specified in the Low Voltage Directive (LVD))</p>	<p>CLASS III Operating with SELV</p>	<p>POWER SUPPLY By remote power supply SELV OUTPUT 24V constant voltage</p>		<p>SEPARATE WASTE COLLECTION OF ELECTRIC AND ELECTRONIC EQUIPMENT</p>	<p>Made in Italy Projected, manufactured and assembled in Italy</p>
--	--	---	--	--	---	--