

N° LED	W	Lm to the light source				R / V / B		
01	4	475	350mA	IP65 on the light source	DIFFUSE	-	-	- 3000K -

Model	Description		Dimensions 300x390mm	Jig positioning for hole	
	<p>On wall Led lamp. Finish: dark bronze color varnished, diffusor: "pulegoso" blown glass, light amber color (with air bubbles incorporated in the thickness of the glass). It is provided with 25 cm bipolar cable for the electrical connection to the remote power supply. Indoor/outdoor installation on any rigid plane surface. Fixing by two screws with 6mm diameter (max 8mm) not supplied by us.</p>				
Tracking of screws positioning and of box compartment for the electrical junctions (with jig positioning if required)	Execution of screw holes (6mm diameter, max 8mm) and of box compartment for the electrical junctions	Carry out watertight electrical junctions in the box	Fix the lamp	Finished work	

Series electrical connection 350mA SELV. Polarity: Brown cable + Blue cable -	Connector compliant with EN 60998-2-1 standards
IP68 connector for example Steab Paguro 5664 or similar.	

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

	Compliant with European standards (EMC, RoHs, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	CLASS III Operating with SELV	POWER SUPPLY By remote power supply SELV OUTPUT 350mA constant current		Separate waste collection of electric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy
--	--	---	--	--	--	--