


N° LED	W	Lm to the light source	A			R / V / B		
03	3.6	330	350mA	IP65	DIFFUSE	-	-	2700K 3000K 4000K

Model	Description	Dimensions Ø40 x L=1800mm with stake		Dimensions Ø40 x L=1800mm with flange		
	<p>Aluminum Led light body. 360° emission light. Finish: faux corten varnished, other colors on request. Diffusor screen: thick white opal polycarbonate, IP65 protection degree in the lighting part. It is provided with 1m neoprene bipolar cable for the electrical connection. Outdoor/indoor installation, assembly: embedded in any type of soil with nylon toe-piece or fixed with specific flange.</p>					<p>FL.100.150</p>

Series electrical connection 350mA SELV.
Polarity: Red cable + Black cable -

Connection: IP68 connector for example Steab Paguro 5664 or similar compliant with EN 60998-2-1 standards



(FACSIMILE)



Connection to be made in a watertight place

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

<p>Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))</p>	<p>CLASS III Operating with SELV</p>	<p>POWER SUPPLY By remote power supply SELV OUTPUT 350mA constant current</p>	<p>Separate waste collection of electric and electronic equipment</p>	<p>Made in Italy Projected, manufactured and assembled in Italy</p>
--	---	--	---	--