



N° LED	W	Lm to the light source				R / V / B		
01	1.2	110	350mA	IP65	DIFFUSE		-	2700K 3000K 4000K
03	3.6	330	350mA	IP65	DIFFUSE		-	2700K 3000K 4000K

Model	Description	Dimensions Ø40 x L=1800mm	
	Aluminum Led light body. 360° emission light. It is provided with 1m neoprene bipolar cables for the electrical connection. Outdoor installation, embedded in any type of soil with nylon toe-piece or other on request.		

Series electrical connection 350mA SELV. Polarity: <b>Red cable +</b> Black cable -	IP68 connector for example Steab Paguro 5664 or similar. Connector compliant with EN 60998-2-1 standards
	 Connection to be made in a watertight place

**ATTENTION:** Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irremediably damaged.

<b>Compliant with European standards</b> <small>(EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))</small>	<b>CLASSE III</b> <small>Operating with SELV</small>	<b>POWER SUPPLY</b> <small>By remote power supply SELV OUTPUT 350mA constant current</small>	<small>Separate waste collection of electric and electronic equipment</small>	<b>Made in Italy</b> <small>Projected, manufactured and assembled in Italy</small>
---	---	---	---	---