



N° LED	W/mt	Lm to the light source				R / V / B		
060	15	-	24V	IP40	DIFFUSE	-	RGB	- - -
120	15	1200	24V	IP40	DIFFUSE	-	-	2700K 3000K 4000K
128	23	3200	24V	IP40	DIFFUSE	-	-	2700K 3000K 4000K

Model	Description	Dimensions 25 x 11 x L mm
	<p>Wall/ceiling recessed T Led bar, maximum size 25 cm, plastic terminals with round or square shape.</p> <p>It is provided with 20cm bipolar cable for the electrical connection. Length on request.</p> <p>Indoor installation on any rigid surface by screws, clips or by specific formwork.</p> <p>Recessed compartment dimensions 23mm, depth 14,5mm.</p>	

With clip	With screws, bar length less than one meter	With formwork on drywall
<p>Graffa di Fissaggio in acciaio</p> <p>Graffa di Fissaggio in acciaio</p>		

Parallel electrical connection 12V/24V Polarity: RED cable + BLACK cable -	Connection: Connector compliant with EN 60998-2-1 standards
	<p>(FACSIMILE)</p>

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

	<p>Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))</p>	<p>CLASS III Operating with SELV</p>	<p>POWER SUPPLY By remote power supply SELV OUTPUT 24V constant voltage</p>	<p>SEPARATE WASTE COLLECTION OF ELECTRIC AND ELECTRONIC EQUIPMENT</p>	<p>Made in Italy Projected, manufactured and assembled in Italy</p>
--	--	---	--	---	--