

HI Project Srl

Via Mario Luciani 4/E - 32032 Feltre (BL)

Barra Riccio

BRC.NN.CO.A.TO.FS



CF - PI e n. isc. reg. imprese 00967030255

N° LED	W/mt	Lm to the light source	-A-			R / V / B	٨)			
060*	15	-	24V	IP40	DIFFUSE	-	RGB	-	-	-	
140*	15	1800	24V	IP40	DIFFUSE	-	-	2700K	3000K	4000K	
128	23	3200	24V	IP40	DIFFUSE	-	-	2700K	3000K	4000K	
*Ava	ilable in double	emission									
Model			Description				Dimensions 42 x 26 x L mm				
9			On wall/ceiling Clam Led Bar with single or double light emission. Finish: black/grey anodized aluminum. Screen: opal/semi- opal/transparent. Stainless steel terminals. It is provided with 25cm bipolar cable for the electrical connection. Maximum length 2000mm (longer lengths on request). Indoor installation on any rigid surface by suitable "L" brackets. Fixing with two screws suitable to the support not supplied by us.								
Assembly								Fixing by bracket ST.031.031 h screws Ø max. 3mm		Fixing by bracket ST.031.014 with screws Ø max. 3mm	
		J				0 1x31x15		0 0 1x14x15			
Parallel electrical connection 24V					ONLY FOR 24V RGB			Connection:			
Polarity: RED cable + BLACK cable -					Connection to the pilot module			Connector compliant with EN 60998-2-1			
					Negative = red Negative = blue Negative = green Positive = black			(FACSIMILE)			
	ATTEN	ION: Before starting all electrical con	nnections, make sure the	at the power suppl	y is not in voltage. If this simply re	le is not respected, t	the lighting sou	irce will be irremediabl	y damaged.		
		pliant with European standards		CLASS III	POWER	m (Separate waste col	lection	Made in Italy		

info@hiproject.it

www.brillamenti.it

Tel. 0439 310098