



N° LED	W/mt	Lm to the light source				R / V / B				
060*	15	-	24V	IP40	DIFFUSE	-	RGB	-	-	-
120*	15	1200	24V	IP40	DIFFUSE	-	-	2700K	3000K	4000K
128*	23	3200	24V	IP40	DIFFUSE	-	-	2700K	3000K	4000K

\* Available in double emission

Model	Description	Dimensions 42 x 26 x L mm
	<p>On wall/ceiling or hanging Clam Led Bar with single or double light emission. Maximum size 42mm, steel terminals. It is provided with 25cm bipolar cable for the electrical connection. Maximum length 2000mm. Indoor installation on any rigid surface by specific "L" brackets. Fixing by two screws not supplied by us.</p>	

<p><b>Parallel electrical connection 12V/24V</b> <b>Polarity: RED cable + BLACK cable -</b></p>	<p><b>Connection:</b> Connector compliant with EN 60998-2-1 standards</p> <p>(FACSIMILE)</p>
---	--

**ATTENTION:** Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irremediably damaged.

	<p><b>Compliant with European standards</b> (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))</p>	<p><b>CLASS III</b> Operating with SELV</p>	<p><b>POWER SUPPLY</b> By remote power supply SELV OUTPUT 24V constant voltage</p>	<p>SEPARATE WASTE COLLECTION OF ELECTRIC AND ELECTRONIC EQUIPMENT</p>	<p><b>Made in Italy</b> Projected, manufactured and assembled in Italy</p>
--	--	---	--	---	--