



N° LED	W	Lm to the Led light source				R / V / B		
03	3.6	330	350mA	IP40	DIFFUSE	-	-	2700K 3000K 4000K
03	10.5	-	350mA See the pilot module	IP40	DIFFUSE	-	RGB	- - -

Model	Description	Dimensions $\varnothing 70 \times 50\text{mm}$	Wall support $\varnothing 61\text{mm}$
	Led lighting body in stainless steel and transparent worked polycarbonate, for wall/ceiling standing. Finish stainless steel, diffusor opal polycarbonate. It is provided with 25cm bipolar cable for the electrical connection. Indoor installation on any rigid plane surface. Pressure fixing with specific aluminum support fixed by two screws not supplied by us.		
Aluminum support fixing with two countersunk screws with maximum diameter 5mm	Electrical connection and pressure fixing of the lamp body on an elastic ring		Finished work

Series electrical connection 350mA SELV. Polarity: RED cable + BLACK cable -	Connection: Connector compliant with EN 60998-2-1 standards	ONLY FOR RGB VERSION Connection to the pilot module
	(FACSIMILE) 	+ = red - = red/black + = blue - = blue/black + = green - = green/black

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

	Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	CLASS III Operating with SELV	POWER SOURCE By remote power supply SELV OUTPUT 350mA constant current / Only for 350mA RGB version, please see the connection to the pilot module		Separate waste collection of electric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy
--	--	---	---	--	--	--