



N° LED	W/mt	Lm metro to the light source				R / V / B		
060	15	-	24V	IP40	DIFFUSE	-	RGB	- - -
140	15	1800	24V	IP40	DIFFUSE	-	-	2700K 3000K 4000K
128	23	3000	24V	IP40	DIFFUSE	-	-	2700K 3000K 4000K

Model	Description	Dimensions 105 x 40 x L mm
	<p>Wall/ceiling flush recessed Led bar. Width of the visible part at finished work: 35mm, steel closing terminals. Diffusor screen: opal.</p> <p>It is provided with 25cm bipolar cable for the electrical connection.</p> <p>Maximum length bar: 2000mm (longer lengths on request).</p> <p>Customized junction angles cutting.</p> <p>Indoor installation on drywall, fixing by screws not supplied by us (screws normally used for drywall).</p>	
Drywall mounting	Fix the bar to the supports and carry out the electrical connection	Fixing on the drywall
		Protect the bar screen with duct tape, carry out the smoothing and the finishing

Parallel electrical connection 24V - Polarity: RED cable + BLACK cable -	ONLY FOR 24V RGB VERSION Connection to the pilot module	Connection: Connector compliant with EN 60998-2-1 standards
	<p>Negative = red</p> <p>Negative = blue</p> <p>Negative = green</p> <p>Positive = black</p>	<p>(FACSIMILE)</p>

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

	Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	CLASS III Operating with SELV	POWER SUPPLY By remote power supply SELV OUTPUT 24V constant voltage / Only for 24V RGB version, please see the power supply to the pilot module		Separate waste collection of electric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy
HI Project Srl	Via Mario Luciani 4/E - 32032 Feltre (BL)	Tel. 0439 310098	info@hiproject.it	www.brillamenti.it	CF - PI e n. isc. reg. imprese 00967030255	