



| N° LED | W/mt | Lm<br>to the light source |     |      |         | R / V / B |     |                   |
|--------|------|---------------------------|-----|------|---------|-----------|-----|-------------------|
| 060    | 15   | -                         | 24V | IP40 | DIFFUSE | -         | RGB | - - -             |
| 140    | 15   | 1800                      | 24V | IP40 | DIFFUSE | -         | -   | 2700K 3000K 4000K |

| Model | Description  | Dimensions 25 x 11 x L mm |
|-------|--|---------------------------|
|       | Wall/ceiling recessed T Led Bar, plastic terminals with round or square shape. Finish: grey anodized aluminum, other colors on request. Screen: opal/transparent. It is provided with 25cm bipolar cable for the electrical connection. Maximum length 2000mm (longer lengths on request). Indoor installation on any flat and rigid surface, fixing by screws, clips or by suitable formwork. |                           |

| Fixing with self-tapping screws, maximum diameter 3mm. Maximum length bar 1,5m | Fixing with formwork CF.013.023 on a drywall with self-drilling screws. |
|--|---|
|  |   |

| Fixing with clip GR.020.012 | Fixing with bracket ST.031.031 by screws maximum diameter 3mm | Fixing with bracket ST.031.014 with screws maximum diameter 3mm |
|-----------------------------|---|---|
|                             |   |   |

| Parallel electrical connection 24V<br>Polarity: <b>RED cable +</b> <b>BLACK cable -</b> | <b>ONLY FOR 24V RGB</b><br>Connection to the pilot module                 | Connection:<br>Connector compliant with EN 60998-2-1<br><b>(FACSIMILE)</b> |
|---|---|--|
|   | Negative = red<br>Negative = blue<br>Negative = green<br>Positive = black |  |

**ATTENTION:** Before starting all electrical connections, make sure that the power supply is not in voltage. If this simply rule is not respected, the lighting source will be irretrievably damaged.

|  |   |   |  |  |
|--|---|---|--|--|
| <b>Compliant with European standards</b><br>(EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD)) | <b>CLASS III</b><br>Operating with SELV | <b>POWER SUPPLY</b><br>By remote power supply SELV OUTPUT 24Vdc constant voltage /<br>Only for 24Vdc RGB version, please see the connection to the pilot module | Separate waste collection of electric and electronic equipment | <b>Made in Italy</b><br>Projected, manufactured and assembled in Italy |
|--|---|---|--|--|