



N° LED double emission	W	Lm to the light source				R / V / B		
↑03 ↓03	7.2	660	350mA	IP55	15° - 40°	-	-	2700K 3000K 4000K

Model	Description		Dimensions 110 x 145 x 60mm
	<p>On-wall Led light body in aluminum and wood. Finish: untreated larch wood, screen: opal/transparent polycarbonate. It is provided with 25cm bipolar cable for the electrical connection. Indoor/outdoor installation on any rigid plane surface. Fixing by two countersunk screws with 4mm diameter not supplied by us.</p>		
With countersunk screws (diameter 4 mm), fix the support to the wall.	Carry out the electrical connection	Fix the lamp to the support	Finished work

<p><b>Series electrical connection 350mA SELV.</b> Polarity: <b>Red cable + Black cable -</b></p>	<p><b>Connection:</b> connector compliant with EN 60998-2-1 standards</p>	
	<p>(FACSIMILE) <b>Indoor connector</b></p>	<p>(FACSIMILE) <b>IP68 connector for example Steab Paguro 5664 or similar</b></p>

**ATTENTION:** Before starting all electrical connections, make sure that the power supply is not powered. If this simple rule is not respected, the lighting source will be irretrievably damaged.

	<p><b>Compliant with European standards</b> (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))</p>	<p><b>CLASS III</b> Operating with SELV</p>	<p><b>POWER SUPPLY</b> By remote power supply SELV OUTPUT 350mA constant current</p>	<p> Separate waste collection of electric and electronic equipment</p>	<p><b>Made in Italy</b> Projected, manufactured and assembled in Italy</p>
--	--	---	--	--	--