



N° LED double emission	W tot.	Lm to the light source				R / V / B				
↑03 / ↑07	3.6 / 8.4	330 / 770	350mA	IP65 in the illuminating part	7° - 25° - 40°	-	-	2700K	3000K	4000K
↓03 / ↓07	3.6 / 8.4	330 / 770	350mA	IP65 in the illuminating part	7° - 25° - 40°	-	-	2700K	3000K	4000K

Model	Description	Dimensions 150 x 210x90mm
	Aluminum and stainless steel Led light body for wall standing. Finish: masking mirrors white ral 9016 varnished, frame: varnished faux corten, other colors on request. Protection screen of the Led: transparent polycarbonate. It is provided with 50cm bipolar cable for the electrical connection. Indoor/outdoor installation on any rigid plane surface. Fixing by four screws 4mm diameter (max.5mm) not supplied by us.	 150x210x90

Define the lamp positioning. <b>ATTENTION: Guarantee the planarity support</b>	Fix the lamp on a wall through four screws with 4mm diameter (max. 5mm)	Carry out the electrical connection	Screw the outer covering structure with the four screws

Series electrical connection 350mA SELV. Polarity: Red cable + Black cable -	Connection: connector compliant with EN 60998-2-1 standards	
	(FACSIMILE) Indoor connector 	(FACSIMILE) IP68 connector for example Steab Paguro 5664 or similar 

**ATTENTION:** Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

	<b>Compliant with European standards</b> (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	<b>CLASS III</b> Operating with SELV	<b>POWER SUPPLY</b> By remote power supply SELV OUTPUT 350mA constant current		Separate waste collection of electric and electronic equipment	<b>Made in Italy</b> Projected, manufactured and assembled in Italy
--	--	---	--	--	--	--