



N° LED	W	Lm to the light source				R / V / B		
14	16.8	1540	350mA	IP65 in the illuminating part	DIFFUSE	-	-	2700K 3000K 4000K

Model	Description	Dimensions 150 x 210x110mm
	Aluminum and stainless steel Led light body for wall standing. Finish: diffusing mirrors: opal white methacrylate, frame: varnished faux corten, other colors on request. It is provided with 50cm bipolar cable for the electrical connection. Indoor/outdoor installation on any rigid plane surface. Fixing by four screws 4mm diameter (max 5mm) not supplied by us.	 150x210x90

Define the lamp positioning. ATTENTION: Guarantee the planarity support	Fix the lamp on a wall through four screws with 4mm diameter (max. 5mm)	Carry out the electrical connection.	Screw the outer covering structure with the four screws

Series electrical connection 350mA SELV. Polarity: Red cable + Black cable -	Connection: connector compliant with EN 60998-2-1 standards	
	(FACSIMILE) Indoor connector 	(FACSIMILE) IP68 connector for example Steab Paguro 5664 or similar

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simple rule is not respected, the lighting source will be irretrievably damaged.

	Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	CLASS III Operating with SELV	POWER SUPPLY By remote power supply SELV OUTPUT 350mA constant current		Separate waste collection of electric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy
--	--	---	--	--	--	--