

N° LED	W	Lm to the light source				R / V / B		
20	24	2500	350mA	IP20	10° - 25° - 40°	-	-	2700K 3000K 4000K

Model	Description	Dimensions 1560 x 35 x 52mm
	Steel Led light body with directable light available in two versions: countertop wall/ceiling or suspended by two steel cables. Finish: black varnished, other colors on request. It is provided with 25cm bipolar cable for the electrical connection, for the suspended application, it is provided with 2 mt cable: transparent or covered by colored tissue (black, red or streaked gray). Indoor installation on any rigid plane surface. Fixing: if it is suspended by two steel cables, if it is countertop by two screws, suitable to the support, not supplied by us.	 1560x35x52

	Accessories
	4641-M
	95227
	96339

Series electrical connection 350mA POLARITY : RED Cable + BLACK Cable -	Connection: Connector compliant with EN 60998-2-1 standards

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	CLASS III Operating with SELV	POWER SUPPLY By remote power supply SELV OUTPUT 350mA constant current	Separate waste collection of electric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy
--	---	--	--	--