



N° LED	W	Lm to the light source				R / V / B		
20	24	2200	350mA	IP20	DIFFUSE – 10° - 25° - 40°	-	-	2700K 3000K 4000K

Model	Descrizione	Dimensions 1560 x 35x52mm
	<p>On-wall/ceiling steel Led light body with directable light. It is provided with 25cm bipolar cable for the electrical connection. Indoor installation on any rigid plane surface. Fixing by two screws not supplied by us. Finish: black varnished – customized RAL varnished.</p>	 1560x35x52

<p><b>Series electrical connection 350mA SELV.</b> Polarity: <b>Red cable + Black cable -</b></p>	<p><b>Connection:</b> connector compliant with EN 60998-2-1 standards</p> <p>(FACSIMILE)</p>
---	--

**ATTENTION:** Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irremediably damaged.

<p><b>Compliant with European standards</b> (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))</p>	<p><b>CLASSE III</b> Operating with SELV</p>	<p><b>POWER SUPPLY</b> By remote power supply SELV OUTPUT 350mA constant current</p>	<p>Separate waste collection of electric and electronic equipment</p>	<p><b>Made in Italy</b> Projected, manufactured and assembled in Italy</p>
--	--	--	---	--