

| | | | | | | | | |
|--------|----|---------------------------|-------|------|-----------------|-----------|---|-------------------|
| N° LED | W | Lm to the light source | | | | R / V / B | | |
| 20 | 24 | 2200 | 350mA | IP20 | 10° - 25° - 40° | - | - | 2700K 3000K 4000K |

| Model | Description | Dimensions 1590x50x70mm |
|-------|--|-------------------------|
| | Steel Led light body available in two versions: countertop wall/ceiling or suspended by two steel cables. Number 20 Led mounted on swivel heads in every N°20 directions independently. Finish: black varnished, other colors on request. It is provided with 25cm bipolar cable for the electrical connection, for the suspended application, it is provided with 2 meters cable: transparent or covered by colored tissue (black, red or streaked grey). Indoor installation on any plane rigid surface. Fixing: if it is suspended by two steel cables, if it is countertop by two screws, suitable to the support, not supplied by us. | 1590x50x70 |

| | | |
|-----------------------------|-------------------------|---|
| <p>WITH BRACKETS</p> | <p>SUSPENDED</p> | Accessories |
| | | <p>4641-M</p> <p>95227</p> <p>96339</p> |

| | |
|---|---|
| <p>Series electrical connection 350mA SELV. POLARITY : RED cable + BLACK cable</p> | <p>Connection: Connector compliant with EN 60998-2-1 standards.</p> <p>(FACSIMILE)</p> |
|---|---|

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

| | | | | |
|--|---|--|---|--|
| <p>Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))</p> | <p>CLASS III Operating with SELV</p> | <p>POWER SUPPLY By remote power supply SELV OUTPUT 350mA constant current</p> | <p>Separate waste collection of electric and electronic equipment</p> | <p>Made in Italy Projected, manufactured and assembled in Italy</p> |
|--|---|--|---|--|