



N° LED	W	Lm to the light source				R / V / B		
01	1.2	110	350mA	IP65	DIFFUSE		-	2700K 3000K 4000K

Modello	Description	Dimensions 350x165	Lighting body adjustment
	<p>Brass Led light body. It is provided with 50cm bipolar cable for the electrical connection. Outdoor installation embedded on any type of soil. FINISH: OXIDIZED – CUSTOMIZED RAL VARNISHED SCREEN: OPAL/TRANSPARENT POLYCARBONATE.</p>		

<p>Series electrical connection 350mA SELV. Polarity: <b>Red cable +</b> Black cable -</p>	<p>IP68 connector for example Steab Paguro 5664 or similar. Connector compliant with EN 60998-2-1 standards</p>
	<p>(FACSIMILE)</p> <p>Connection to be made in a watertight place</p>

**ATTENTION:** Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

<p><b>Compliant with European standards</b> (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))</p>	<p><b>CLASSE III</b> Operating with SELV</p>	<p><b>POWER SUPPLY</b> By remote power supply SELV OUTPUT 350mA constant current</p>	<p>Separate waste collection of electric and electronic equipment</p>	<p><b>Made in Italy</b> Projected, manufactured and assembled in Italy</p>
--	--	--	---	--