




N° LED	W	Lm to the light source	Luminous efficiency	Chromatic deviation	CRI	IP65 (to the light source)	18°-36°-60°	R / V / B		
01x3	9x3=27	1135x3	125Lm W	SDCM 2	80	total protection against the dust protected against the water splashes		-	-	2700K – 3000K – 4000K

\* The above data refer to a temperature of 3000K

Model	Description	Dimensions	Suggestion for the ground fixing
	<p>Floor Led light body in stainless steel.</p> <p>The three stems support floodlights that can be positioned in all directions. It is provided with three 1m long neoprene bipolar cables more than the lamp for the electrical connections that must be made in a watertight environment.</p> <p>Having three power cables, one for each floodlight, the ignition can be divided as desired by connecting more than one power supply.</p> <p>Finish: faux corten varnished, other colors on request.</p> <p>Screen: transparent polycarbonate.</p> <p>Ground indoor/outdoor installation on flat and stable support sized no less than 300mm x 300mm, suitable to support the weight of the light body of 24Kg and of its height 2mt.</p> <p>Fixing by four screws suitable for the support not supplied by us.</p>		<p>SEE DETAIL A</p> <p>L= Dimension to be defined in the building site for guarantee the lamp stability</p> <p>Min. 200 x 200</p> <p>200 Screw Linchpin M12</p> <p>Min 300x300</p> <p>Watertight box fill with gel</p> <p>The sizes are indicated in mm</p>

**ELECTRICITY SUPPLY: 500mA constant current SELV POWER SUPPLY, not included, remotely placed.**

Series electrical connection. POLARITY: **RED Cable + BLACK Cable-** // **BROWN Cable + light blue CABLE -**



**Connection: Connector compliant with EN 60998-2-1**

**ATTENTION**

The protection degree of the connection system must be identical or greater than the protection degree of the product. The junction clips are not included. The installation must be carried out by qualified personnel.

**IP68 connector for outdoor use: (FACSIMILE)**



● **ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. The connection to the electricity grid must be carried out only after completing the wiring of all the components. If this simply rule is not respected, the lighting source will be irremediably damaged. The installation must be carried out by qualified personnel.**

Compliant with European standards EMC – RoHS – REACH - Ecodesign	It must not be provided with a electrical ground of protection	DIMMABLE By dimmable power supply	OPERATING TEMPERATURE -20°C +40°C	Separate waste collection of electric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy
--	--	-----------------------------------	-----------------------------------	--	--

## Suggestion for the ground fixing

<p><b>Make the support base of adequate size and weight to guarantee the stability of the lamp by placing a watertight well alongside for the electrical connection</b></p>	<p><b>Fix the lamp and adjust it with the nuts located under the lamp plate</b></p>	<p><b>Final result</b></p>	

## WARNING AND PROVISIONS

### ATTENTION!

The appliance safety is guaranteed only by respecting, both during installation and employment phase, of the following instructions. It is therefore necessary to archive the present document.

### WARNINGS:

- The power supply voltage must be removed during the installation and during any operation.
- The appliance must not be modified or tampered with in any way. Every modification can compromise the safety of the appliance, making it dangerous. Hi.Project srl refuses any responsibility for modified or tampered with products. Modifications or tampering with the product, if not authorized by the company (Hi.Project s.r.l.), nullify any direct and indirect responsibility of the manufacturer as well as the warranty.
- The appliance is free from the photobiological risk. Please follow the instructions of this data sheet.
- The product is to be considered a "Containing Product" and is not subject to maintenance. The light source can only be replaced by the manufacturer. For further information please contact Hi.Project s.r.l.
- If the flexible power cable is damaged, it can be substituted only by the manufacturer. For further information please contact Hi.Project s.r.l.
- Each product, at the end of its life, must be committed to a waste storage center specialized in electrical and electronic equipment. Alternatively, it can be returned to the manufacturer.

### WARRANTY CONDITIONS:

Our products are guaranteed for 24 months from the date of purchase. The warranty only covers construction defects attributable to the manufacturer. The warranty does not include all the activities necessary for the product to arrive free port at the manufacturer for repair. The warranty is void if the malfunction is due to: improper use of the product, tampering, repairs not authorized by Hi. Project S.r.l., negligence of the installer, failure to comply with the product rating plate, damage due to natural causes such as lightning or power surges, use of power supplies or drivers not approved by Hi. Project S.r.l. and/or in any case not compliant with the technical regulations that regulate the European market, damage caused by wrong connections or connections with an IP degree lower than the purchased product, damage caused during the transport (even if the transport is organized by Hi. Project S.r.l. on behalf of the Customer), other causes that are not expressly and unequivocally referred to the defectiveness of the product itself.

### PRODUCT CLEANING INSTRUCTIONS

- To clean the appliance, use exclusively a soft cloth, possibly moistened with water and neutral soap.
- Warning: do not use aggressive cleansers, alcohol or solvents.

The information contained in this document may be changed by Hi.Project s.r.l. at any time without notice and does not imply the assumption, even implicit, of any obligation on the part of Hi. Project Srl.

Hi. Project Srl refuses all responsibility if the installation is not carried out by qualified personnel and in compliance with current regulations.

9W 500mA 3000°K



Cree LED, inc.

CXB1512-0000-000ggZnm30H



13 kWh/1000h



2019/2015

