



N° LED	W	Lm to the light source				R / V / B		
01	1,2	110	350mA	IP40	7° - 25° - 40°	• • •	-	2700K 3000K 4000K
03	3,6	330	350mA	IP40	7° - 25° - 40°	-	-	2700K 3000K 4000K

Model	Description	Dimensions Ø35x70mm	Housing holes	
	Recessed flush with the ceiling, aluminum Led light body. 12mm backward light source. Finish: silver grey anodized, other colors on request. Screen: transparent polycarbonate. It is provided with 25cm bipolar cable for the electrical connection. Indoor installation: on wood with Ø 30mm hole, on drywall with formwork, on other materials difficult-to-machine with reference ring to be glued. Pressure assembly, depth in size 80mm.		Formwork CF.030. 040 Hole Ø 40mm 	Ring CF.035. 015 Hole Ø 35mm

Drill the hole 40mm diameter, insert the formwork and fix it with two screws	Insert the ring and glue it to the support	Carry out the finish of the ceiling being careful to keep the spotlight housing perfectly clean	Carry out the electrical connection respecting the polarity. Insert in position the spotlight	Final result	

Series electrical connection 350mA SELV. POLARITY: RED cable + BLACK cable -	Connection: Connector compliant with EN 60998-2-1 standards.
	(FACSIMILE)

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	CLASS III Operating with SELV	POWER SUPPLY By remote power supply SELV OUTPUT 350mA constant current.	Separate waste collection of electric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy
--	---	---	--	--