
















N° LED	W	Lm to the light source				R / V / B		
01	9	1060	500mA	IP40	20° - 35° - 50°	-	-	2700K 3000K 4000K

Model	Description	Dimensions Ø67 x 83 mm	Hole for fixing on wood Ø65mm	Hole for fixing on drywall Ø75 mm	Hole for fixing on masonry Ø80mm
	Recessed flush with the ceiling aluminum Led light body. Finish: silver grey anodized, white Ral 9016 varnished, other colors on request. Screen: transparent polycarbonate. It is provided with 25cm bipolar cable for the electrical connection. Indoor installation: on wood with Ø65mm hole, on drywall with 13mm thickness in special formwork, on masonry with Ø80mm hole. Useful depth: 130mm on masonry, 100mm on drywall and on wood. Assembly with torsion springs.		 Hole Ø 65 mm	 CF.064.073	 CF.064.120S

INSTALLATION ON DRYWALL

				
Drill the hole Ø75mm and insert the formwork	Fix the formwork on the drywall with two screws	Carry out the finish of the ceiling	Carry out the electrical connection respecting the polarity. Insert in position.	Final result.

Series electrical connection 350mA -500mA SELV. POLARITY: RED cable + BLACK cable -

Connection: Connector compliant with EN 60998-2-1 standards



(FACSIMILE)



ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.



Compliant with European standards
(EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))

CLASS III
Operating with SELV

POWER SUPPLY
By remote power supply SELV OUTPUT 350mA-500mA constant current.



Separate waste collection of electric and electronic equipment

Made in Italy
Projected, manufactured and assembled in Italy