



N° LED	W	Lm to the light source				R / V / B		
03	3.6	330	350mA	IP40	DIFFUSE	-	-	2700K 3000K 4000K
01	4,2	-	350mA	IP40	DIFFUSE	-	RGBW	- - -

Model	Description	Dimensions Ø 72x15mm	Hole for fixing Ø65mm
	Recessed on low thickness, Led light body in aluminum. Finish: silver grey anodized aluminum, other finishes on request, screen: opal polycarbonate. It is provided with 25cm cable for the electrical connection. Indoor installation on any rigid surface. Fixing with snap ring on 64mm diameter compartment, depth 15mm.		 Hole Ø 65 mm

Drill the housing hole Ø65mm	Carry out the electrical connection respecting the polarity. Insert in position.	Final result

Series electrical connection 350mA SELV. POLARITY: <b>RED cable +</b> <b>BLACK cable -</b>	Connection: Connector compliant with EN 60998-2-1 standards.	POLARITY RGBW:
	(FACSIMILE) 	<b>WHITE LED (+ = GREY) (- = WHITE)</b> <b>RED LED (+ = BLACK) (- = RED)</b> <b>GREEN LED (+ = TRANSPARENT) (- = GREEN)</b> <b>BLUE LED (+ = BROWN) (- = BLUE)</b>

**ATTENTION:** Before starting all electrical connections, make sure that the power supply is not powered. If this simple rule is not respected, the lighting source will be irretrievably damaged.

<b>Compliant with European standards</b> (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	<b>CLASS III</b> Operating with SELV	<b>POWER SUPPLY</b> By remote power supply SELV OUTPUT 350mA constant current. For 350mA RGB please see the pilot module power supply.	Separate waste collection of electric and electronic equipment	<b>Made in Italy</b> Projected, manufactured and assembled in Italy
--	---	--	--	--