

N° LED	W	Lm to the light source				R / V / B		
12	5	355	24V	IP65	DIFFUSE	-	-	2700K 3000K 4000K

Description: Wall recessed Led light body in aluminum. It is provided with 25cm bipolar cable for the electrical connection. Finish: hard anodized aluminum in dark grey color. Screen: sandblasted polycarbonate. Indoor/outdoor installation on any rigid surface with suitable formwork. Fixing with “spring ball” system without screws in view.

Model	Dimensions 197x70x2mm	Fixing formwork 173x80x58mm

Fix the formwork flush with the finished wall. ATTENTION: THE FORMWORK MUST NOT BE REENRANT RESPECT FLUSH WALL	Carry out the electrical connection and with a light pressure insert the Led light body into the formwork	Final result

<p>Parallel electrical connection 24V Polarity: RED cable + BLACK cable -</p>	<p>Polar diagram</p>	<p>Connection: connector compliant with EN 60998-2-1 standards (FACSIMILE)</p> <p>IP68 connector for example Steab Paguro 5664 or similar</p>
---	-----------------------------	--

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

	Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	CLASS III Operating with SELV	POWER SUPPLY By remote power supply SELV OUTPUT 350mA constant current		Separate waste collection of electric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy
--	--	---	--	--	--	--