

Tulip

TM.NN.000.OTA.FI



OFFICINA DELLA LUCE

									I
N° LED	W	Lm to the light source	-A-				R / V / B		• · · · · • · • • • • • • • • • • • • •
01	1.2	110	350mA	IP40	25°	•	-	-	2700K 3000K 4000K
	ſ	/lodel		Description			Dimensions		
F S It Ir F			Stainless steel Led light body on a flexible stem, wall mounted. Finish: rigid parts in stainless steel, flexible part in satin nickel. Screen: transparent polycarbonate. It is provided with 25cm bipolar cable for the electrical connection. Indoor installation on any rigid surface. Fixing by stainless steel inclined block and two screws not in view (not supplied by us) suitable for the support.			h=31 24x20			
Cathe Dassage Co 17 17 Cathe Dassage Co 17 17 17									
Fixing screws scheme and cables passage		Drill the panel	Carry out the electrical connection		Fix b	by posterior screws		Final result	
	Serie	s electrical connection 35		Connection: Connector compliant with EN 60008 2.1 standards					
RED cable + BLACK cable -					Connection: Connector compliant with EN 60998-2-1 standards.				
=			*-	(FACSIMILE)					
ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irremediably damaged.									
		iant with European standards n and requirements specified in the Low Voltage (LVD)	e Directive CLASS III Operating with SELV				Separate waste col of electric and elec equipment		Made in Italy Projected, manufactured and assembled in Italy
HIF	Project Srl	Via Mario Luciani 4/E - 32032 Fel	tre (BL) Tel. 04	439 310098	<u>info@hiproject.it</u>	www	.brillamenti.it	CF -	PI e n. isc. reg. imprese 00967030255