



N° LED	W	Lm to the light source				R / V / B		
01	1.2	110	350mA	IP40	25°	-	-	2700K 3000K 4000K

Model	Description	Dimensions
	<p>Stainless steel Led light body on a flexible stem, wall mounted. Finish: rigid parts in stainless steel, flexible part in satin nickel. Screen: transparent polycarbonate. It is provided with 25cm bipolar cable for the electrical connection. 120mmx75mm stainless steel rectangular fixing element with provided touch switch. Indoor installation on any rigid surface or on three modules recessed flush mounting box. Fixing by two visible screws.</p>	

Fixing three modules rectangular box - distance between the screw holes 83,5mm	Carry out the electrical connection and fix two screws	Final result

<p>Series electrical connection 350mA SELV. POLARITY: RED cable + BLACK cable -</p>	<p>Connection: Connector compliant with EN 60998-2-1 standards.</p>

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	CLASS III Operating with SELV	POWER SUPPLY By remote power supply SELV OUTPUT 350mA constant current	Separate waste collection of electric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy
--	---	--	--	--