



N° LED	W	Lm to the light source				R / V / B		
03	3.6	330	350mA	IP20	DIFFUSE	-	-	2700K 3000K 4000K

Model	Description	Dimensions Ø80x110mm	Hole for fixing Ø50mm	Formwork on masonry
	Wall and ceiling recessed Led light body in aluminum and blown glass. Finish: satinized milk white glass. Diffusor: white opal blown glass. It is provided with 25cm bipolar cable for the electrical connection. Indoor installation on any rigid surface. Fixing with torsion springs on 50mm diameter compartment, 40mm depth.			

Drill the hole Ø50mm	Carry out the electrical connection and insert in position	Final result

<p>Series electrical connection 350mA SELV. POLARITY: RED cable + BLACK cable -</p>	<p>Connection: Connector compliant with EN 60998-2-1 standards</p>
	(FACSIMILE)

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

	Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	CLASS III Operating with SELV	POWER SUPPLY By remote power supply SELV OUTPUT 350mA constant current		Separate waste collection of electric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy
--	--	---	--	--	--	--