



N° LED	W	Lm to the light source				R / V / B		
3	19	2226	350mA	IP40	DIFFUSE	-	-	2700K 3000K 4000K

Model	Description	Dimensions	Magnets position Ø 25 x 7 mm
	On-wall/ceiling Led light body. Finish: satinized milk white glass, the metallic visible part white Ral 9016 varnished. Diffusor: white opal blown glass. Support flange in aluminum, it is provided with 25cm bipolar cable for the electrical connection. Ceiling/wall installation three neodymium magnets.		

Define the fixing point	Fix the magnets and make sure they are perfectly coplanar	Carry out the electrical connection	Final result

Series electrical connection 350mA SELV - Polarity: <b>RED cable +</b> <b>BLACK cable -</b>	<b>Connection:</b> Connector compliant with EN 60998-2-1 standards <b>(FACSIMILE)</b>

**ATTENTION:** Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

	<b>Compliant with European standards</b> (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	<b>CLASS III</b> Operating with SELV	<b>POWER SUPPLY</b> By remote power supply SELV OUTPUT 350mA constant current		Separate waste collection of electric and electronic equipment	<b>Made in Italy</b> Projected, manufactured and assembled in Italy
--	--	---	---	--	--	--