

N° LED	W	Lm to the light source				R / V / B		
01	9	1060	500mA	IP40	DIFFUSE	-	-	2700K 3000K 4000K

Model	Description	Dimensions Ø124x170mm	Fixing with countersunk screw Ø5mm
	Ceiling hanging Led light body in aluminum and blown glass. Finish: satinized milk white glass, the visible parts white Ral 9016 varnished. Diffusor: white opal blown glass. It is provided with 1,5m bipolar cable in fabric, available colors: black, red or streaked grey, for the electrical connection. Indoor installation on any rigid surface. Fixing with two screws, not supplied by us, suitable for the support.		

Power cables connected to the remote power supply	Carry out the electrical connection respecting the polarity	Define the distance of the Led lighting body to the ceiling by locking with cable clamp and fix the rosette to the ceiling by two screws	Final result

<p>Series electrical connection 350mA - 500mA SELV.</p> <p>POLARITY: RED cable + BLACK cable -</p>	<p>Connection:</p> <p>Connector compliant with EN 60998-2-1 standards</p>

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

	Compliant with European standards (EMC, RoHs, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	CLASS III Operating with SELV	POWER SUPPLY By remote power supply SELV OUTPUT 350mA-500mA constant current		Separate waste collection of electric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy
--	--	---	--	--	--	--