



N° LED	W	Lm to the light source				R / V / B		
07	9	1060	48V	IP20	20° - 35° - 50°	-	-	2700K 3000K 4000K

Model	Description	Dimensions Ø 60 x 120mm
	Aluminum Led floodlight for the installation on electrified bar. Finish: white Ral 9016 varnished, other colors on request. Screen: transparent polycarbonate. It is provided complete with suitable adaptor, equipped with converter, for the connection to the electrified track. The ZPro floodlight must be inserted in electrified tracks company "Stucchi" with the codes indicated below or in other types identical for the shape characteristics and for the electric power supply.	

ST1	ST13	ST8	Hook in position the floodlight	Disassembly modality of the floodlight from the housing seat	Final result
Type of electrified tracks			Electrical connection by the track extremity 48V		Floodlight connection by rapid hook

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

	Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	CLASS III Operating with SELV	POWER SUPPLY By electrified track powered 48Vdc SELV		Separate waste collection of electric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy
--	--	---	--	--	--	--