



N° LED	W	Lm to the light source				R / V / B		
03	3.6	360	350mA	IP20	40°	-	-	2700K 3000K 4000K

Model	Description	Dimensions Ø57 x 62 mm	Hole for fixing Ø 50mm
	Ceiling and hidden aluminum Led light body. Projection of the variable light angle by adjusting the Led light body depth inside the casing. Finish: black or grey anodized, screen: transparent polycarbonate. It is provided with 25cm bipolar cable for the electrical connection. Indoor installation on any rigid surface, diameter compartment 50mm, depth 60mm. Pressure assembly with spring.		 Hole Ø 50 mm
Define the position and drill Ø50mm	Insert the body of the spotlight, without the LED holder body, into the hole.	Carry out the electrical connection respecting the cables polarity.	Insert the spotlight. It is recommended to grease inside the formwork with a little bit of oil or of neutral grease before inserting the spotlight. Positioning of the spotlight with suitable supplied tong.

Series electrical connection 350mA SELV. Polarity: Red cable + Black cable -	Connection: connector compliant with EN 60998-2-1 standards

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	CLASS III Operating with SELV	POWER SUPPLY By remote power supply SELV OUTPUT 350mA constant current	Separate waste collection of electric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy
--	---	--	--	--