



N° LED	W/mt	Lm/mt to the light source				R / V / B		
140	15	1800	24Vdc	IP20	DIFFUSE	-	-	2700K 3000K 4000K

Model	Description	Dimensions Ø40,5xL	Hooking system
	Ceiling hanging Led light body in aluminum and polycarbonate. Finish: metal part silver grey or black anodized aluminum, other colors/finishes on request. Tubular diffuser: opal white. It is provided with 50cm cable covered by colored fabric, available color: black or red, for the electrical connection. Maximum length 2000mm (longer lengths on request). Indoor installation on any rigid surface. Hanging assembly with rigid support and bracket. Bracket must to be fixed on the ceiling with a countersunk screw with maximum diameter 5mm, not supplied by us.		

Fix the support to the ceiling with a countersunk screw with maximum diameter 5mm suitable to the support	Carry out the electrical connection respecting the cables polarity	Hook the lamp body to the support	Final result

<b>Parallel electrical connection 24Vdc. Polarity: Red cable + Black cable -</b>	<b>Connection:</b> connector compliant with EN 60998-2-1 standards <b>(FACSIMILE)</b>

**ATTENTION:** Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

	<b>Compliant with European standards</b> (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	<b>CLASS III</b> Operating with SELV	<b>POWER SUPPLY</b> By remote power supply SELV OUTPUT 24Vdc constant voltage		Separate waste collection of electric and electronic equipment	<b>Made in Italy</b> Projected, manufactured and assembled in Italy
--	--	---	--	--	--	--