



N° LED	W max	Lm to the light source				R / V / B		
03	10.5	-	350mA	IP65	DIFFUSE - 40°	-	RGB	- - -
01	6,3	742	350mA	IP65	20° - 35° - 50°	-	-	2700K 3000K 4000K

Model	Description	Dimensions Ø110 x 60 mm	Fixing formwork Ø110x91mm	Installation		
	Recessed floor Led light body in aluminum and stainless steel. It is provided with 50cm neoprene bipolar cable for the electrical connection. Finish: stainless steel satinized in view, screen: thick transparent polycarbonate. Floor outdoor/indoor installation with specific formwork, depth dimension 91mm. Fixing by two screws suitable for the support, not supplied by us.					
				Position and fix the formwork flush with the floor	Carry out the electrical connection and fix the lighting body with 2 screws	Final result

Series electrical connection 350mA SELV. Polarity: RED cable + BLACK cable -	ONLY FOR 350mA RGB VERSION Connection to the pilot module	Connection: connector compliant with EN 60998-2-1 standards
	<p>+ = red - = red/black</p> <p>+ = blue - = blue/black</p> <p>+ = green - = green/black</p>	<p>(FACSIMILE)</p> <p>IP68 connector for example Steab Paguro 5664 or similar</p>

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

	Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	CLASS III Operating with SELV	POWER SUPPLY By remote power supply SELV OUTPUT 350mA constant current		Separate waste collection of electric and electronic equipment	Made in Italy Projected, manufactured and assembled in Italy
--	--	---	--	--	--	--