



| N° LED | W | Lm to the light source | | | | R / V / B | | |
|--------|-----|---------------------------|------------------------------|------|--------------------------|-----------|-----|-------------------|
| 03 | 3.6 | 330 | 350mA / 12V (only RGB) / 24V | IP65 | DIFFUSE - 7° - 25° - 40° | - | RGB | 2700K 3000K 4000K |
| 07 | 8.4 | 770 | 350mA / 24V | IP65 | DIFFUSE - 7° - 25° - 40° | - | - | 2700K 3000K 4000K |

| Model | Description | Dimensions Ø110 x 60 mm | Fixing formwork Ø110 x 91mm |
|-------|---|-------------------------|-----------------------------|
| | <p>Recessed floor Led light body in aluminum and stainless steel. It is provided with 50cm neoprene bipolar cable for the electrical connection. Floor outdoor installation with specific formwork. Fixing by two screws, depth dimension 91mm. FINISH: STEINLESS STEEL SATINIZED SCREEN: OPAL / TRASPARENT POLYCARBONATE</p> | | |

| Series electrical connection 350mA SELV. Polarity: Red cable + Black cable - | Parallel electrical connection 12V / 24V. Polarity: Red cable + Black cable - | Connection to be made in a watertight place: connector compliant with EN 60998-2-1 standards (FACSIMILE) |
|---|--|---|
| | | IP68 connector for example Steab Paguro 5664 or similar |

ATTENTION: Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

| | | | | |
|--|--|--|--|--|
| Compliant with European standards (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD)) | CLASSE III Operating with SELV | POWER SUPPLY By remote power supply SELV OUTPUT 350mA constant current/ By remote power supply SELV OUTPUT 24V constant voltage | Separate waste collection of electric and electronic equipment | Made in Italy Projected, manufactured and assembled in Italy |
|--|--|--|--|--|